

## Revoslot Challenge Rules – GTSLOTS Weekend Racing Series



**Marcos**



**Porsche 911**



**Viper**



**Supra**

**MOTOR:** Stock, and wrapper must be intact

**CHASSIS:** Stock

**BODY:** Stock. Wing must be attached onto car at race start.

**INTERIOR:** Stock, no modifications

**WHEELS:** Stock (must be from specific car wheel came on, and cannot swap Porsche with Viper, etc.)

Must have inserts that pertain to the car. Inserts may be painted.

**FRONT AXLE BLOCK:** May use either front location for front axle blocks. May not switch rear blocks with front or vice-versa.

**FRONT TIRES:** Stock fronts, may true for roundness. Excessive sanding judged by tech inspector not allowed.

**REAR TIRES:** Quick Slicks silicone only. Porsche/Marcos: RS75; Viper/Supra: TS43. (Vipers and Supra May run RS75 with o-ring)

**GUIDE:** Stock/Stock wood guide; slight sanding to clean edges and burrs allowed.

**BRAID:** Any

**LEAD WIRE:** Stock

**AXLES:** Stock

**WHEEL BASE WIDTH:** Wheels may not pass fenders when viewed from above with body on car. Any manufacture spacers allowed.

**SPUR GEAR:** Stock

**PINION GEAR:** Stock or any Slot.IT 12T 6.5mm/6/75mm/7mm (due to early model issues)

**SCREWS:** Stock( First release Porsche motor pod screws may be changed to not hang below chassis)

**BEARINGS:** Stock

**WEIGHT:** Any manufacture, must be inside car